



Main

Product or component type	Complete joystick controller
Product specific application	Medium hoisting applications
Device short name	XKDF
Sale per indivisible quantity	1

Complementary

Bezel material	Metal
Fixing collar material	Metal
Protective treatment	TC
Operator position information	All positions
Positive opening	Slow break, double-break with
Connections - terminals	Captive screw clamp terminals, $\leq 2 \times 1.5 \text{ mm}^2$ with cable end Captive screw clamp terminals, $\leq 1 \times 2.5 \text{ mm}^2$ without cable end Captive screw clamp terminals, $\geq 1 \times 0.5 \text{ mm}^2$
Short-circuit protection	10 A cartridge fuse EN/IEC 60947-5-1
[Ith] conventional free air thermal current	10 A EN/IEC 60947-5-1 10 A CSA C22.2 No 14
[Ui] rated insulation voltage	500 V 3)IEC 60947-1

Environment

Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Overvoltage category	Class I IEC 61140
IP degree of protection	IP54 IEC 60529
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14
Product certifications	CSA EAC CCC
Mechanical durability	3000000 cycles
Vibration resistance	2 gn 10...500 Hz)IEC 60068-2-6
Shock resistance	15 gn 11 ms) IEC 60068-2-27

Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS
Discount Schedule	I
GTIN	00785901303374
Package weight(Lbs)	5 lb(US) (2.27 kg)
Returnability	No
Country of origin	FR

Contractual warranty

Warranty	18 months
----------	-----------