



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	90 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Auxiliary Contacts	2 NO
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	3
Maximum Height	11.10 in (282 mm)
Maximum Depth	6.50 in (165 mm)
Maximum Width	5.98 in (152 mm)

Environment

Enclosure Type	Not rated (open device)
Product certifications	UL Listed NEMA CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	07859010851888
Package weight(Lbs)	17 lb(US) (7.71 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------