



Main

Product	Well-Guard Control
Type	S2
Device application	Pumping

Complementary

Control Circuit Type	Separate control circuit
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	27 A
Number of Poles	3
Horsepower Rating	10 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	30 A
Fuse type	H or K
Thermal overload type	Melting alloy
Protection type	Overload
Device mounting	Surface
Electrical connection	Screw terminal
NEMA size	1
Maximum Height	38.50 in (978 mm)
Maximum Width	20.43 in (519 mm)
Maximum Depth	9.41 in (239 mm)

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA

Ordering and shipping details

Category	21393 - 8940 WC,WD
Discount Schedule	CP1
GTIN	00785901316398
Package weight(Lbs)	92 lb(US) (41.73 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------