



Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	12

Complementary

Number of ways	3 ways Aux + 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	2.48 in (63 mm)
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	80 A 104 °F (40 °C)
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz UL 508
[Uimp] rated impulse withstand voltage	12 kVUL 508
Mounting mode	Horizontal
Mounting location	Top tunnel type terminals
9 mm pitches	24
Maximum Width	8.50 in (216 mm)
Color	White RAL 9001)
Range compatibility	Multi 9 C60 C60 UL489

Environment

Standards	UL 508
Fire resistance	1760 °F (960 °C) 30 s) UL 508

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	03606480385957
Nbr. of units in pkg.	1
Package weight(Lbs)	0.25 lb(US) (0.11 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.13 in (5.4 cm)
Package 1 width	4.41 in (11.2 cm)
Package 1 Length	9.13 in (23.2 cm)

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------