8501KUR13P14V20

Plug in relay, 11 blade, 3PDT, 10 amp at 277 VAC, 120 VAC coil, pilot light





Main	
Product range	8501K
Product type	Relay
Relay type	General purpose
Mounting type	Socket
Contact composition	3PDT
[Uc] control circuit voltage	120 V AC
Pilot light	Indicator light relay energised LED

C	_ _			
Com	one	me	man	V
00	ρ.υ			J

Horsepower rating	1 Hp 277 V AC 0.33 hp 120 V AC	
Breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 277 V AC resistive control circuit UL 508 10 A 30 V DC resistive control circuit UL 508	
Maximum switching voltage	300 V AC 30 V DC	
Contact material	Silver alloy (AgNi)	
Operating time	20 ms - pick-up 20 ms - drop-out	
Shape of pins	Spade	
For use with	8501NR82	

Environment

Environment		
Ambient temperature range - operational	-40131 °F (-4055 °C)	
Product certifications	UL Listed UL Recognized CSA RoHS CE	
Maximum Height	2.25 in (57.15 mm)	
Maximum Width	1.37 in (34.80 mm)	
Maximum Depth	1.4 in (35.56 mm)	

Ordering and shipping details

Category	21144 - 8501 KU	
Discount Schedule	CP2	
GTIN	00785901981756	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.2 lb(US) (0.09 kg)	
Returnability	Yes	
Country of origin	CN	

Packing Units

Package 1 Height	1.70 in (4.318 cm)	
Package 1 width	1.70 in (4.318 cm)	
Package 1 Length	3.00 in (7.620 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	