



Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	440 V AC 50 Hz 480 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	270 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	5
Maximum Height	17.56 in (446 mm)
Maximum Depth	8.74 in (222 mm)
Maximum Width	8.54 in (217 mm)

Environment

Enclosure Type	Not rated (open device)
Product certifications	NEMA CSA UL Listed

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901854739
Nbr. of units in pkg.	1
Package weight(Lbs)	55.9 lb(US) (25.36 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	10.10 in (25.654 cm)
Package 1 width	11.00 in (27.940 cm)
Package 1 Length	19.60 in (49.784 cm)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------