



Overview

Lead time Special Order - Call for Quoted Lead Times

General

Provided equipment EcoStruxure IT ready (UPS)

Physical

Color	White
Maximum Depth	300.00 in (762 cm)
Maximum Height	118.11 in (300 cm)
Net Weight	22046.24 lb(US) (10000 kg)
Number of racks	6
Rack Free Space	252
Number of rack unit	42U
Maximum Width	137.99 in (350.5 cm)

Input

Nominal Input Voltage 3 phase

Output

Kw Rating	35000 W
KW per Rack	5.8 kW
Output voltage	208 V 3 phase
PDU Amp Capacity	24 A
PDU Type	Metered
Max Configurable Power (Watts)	40000 W
Configured Power	35000 W

Conformance

Product certifications CUL Listed
UL Listed

Environmental

Ambient air temperature for operation	-13...104 °F (-25...40 °C)
Operating altitude	0...1500 ft

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery type	VRLA
Liquid Electrolyte Value	0
Battery Volt-Amp-Hour Capacity	0 VAh

Communications & Management

Emergency Power Off (EPO)	Optional
---------------------------	----------

Ordering and shipping details

Nbr. of units in pkg.	1
-----------------------	---

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------