

Main

Asynchronous motor control profile	Variable torque standard
Device short name	ATV61
Range of product	Altivar 61

Complementary

Line Rated Current	88 A
Cable entry	Type 1 conduit entry outdoor
Communication port protocol	Modbus CANopen LonWorks
Input voltage	208/240 V AC
Keypad type	LCD keypad
Maximum Horse Power Rating	30 hp
Motor power kW	22 kW
Phase	3 phase output 1 phase input

Environment

EMC filter	Without EMC filter
IP degree of protection	IP20
NEMA degree of protection	No enclosure rating (open device)
Protective treatment	None

Ordering and shipping details

Category	22137 - ATV61 7.5 THRU 50 HP DRIVES
Discount Schedule	CP4C
Package weight(Lbs)	55 lb(US) (24.95 kg)
Returnability	No
Country of origin	CN

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company. This information is not intended to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.