

### Main

Marketing Trade Name	QO
Product	Load Center
Cover type	Order separately

### Complementary

Tightening torque	Cover 20 lb.in
Load Center Type	Main breaker
Line Rated Current	125 A
Number of spaces	30
Short Circuit Current Rating	25 kA
Maximum Number of Single Pole Circuits	30
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC
Wire Size	AWG 4...300 kcmil aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire 4-wire
Busbar Material	Tin plated copper busbar
Enclosure Material	Welded sheet steel
Cover Finish	Baked enamel Gray
Box number	12
Maximum Height	39.37 in (1000 mm)
Maximum Width	14.25 in (362 mm)

### Environment

Enclosure Rating	NEMA 1 indoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL Listed

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901290520
Nbr. of units in pkg.	1
Package weight(Lbs)	25.43 lb(US) (11.53 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Package 1 Height	0.41 ft (0.124 m)
Package 1 width	1.22 ft (0.373 m)
Package 1 Length	3.37 ft (1.026 m)


## Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty


Warranty	18 months
----------	-----------

Approximate Dimensions




KNOCKOUTS							
SYMBOL	A	B	C	D	E	F	G
IN	.50	.75	1.00	1.25	1.50	2.00	2.50
MM	13	19	25	32	38	51	64

## Connections and Wiring Diagrams



QO330MQ125  
QO330MQ150  
QO330MQ200



QO342MQ150  
QO342MQ200  
QO342MQ225