



### Overview

Lead time	Usually in Stock
-----------	------------------



### General

Provided equipment	Installation guide Rack Mounting brackets
--------------------	--

### Physical

Cable length	12 ft (3.66 m)
Color	Black
Maximum Depth	2.24 in (5.7 cm)
Maximum Height	1.73 in (4.4 cm)
Net Weight	5.51 lb(US) (2.5 kg)
Maximum Width	17.60 in (44.7 cm)

### Input

Line Rated Current	16 A
Input current limits	20 A
Load Capacity	3328 VA
Input Frequency	50/60 Hz
Plug standard	NEMA L6-20P
Nominal Input Voltage	200 V 208 V 230 V

### Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

### Conformance

Product certifications	CUL Listed UL Listed
Standards	UL 60950

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

GTIN	00731304213048
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

## Packing Units

Package 1 Height	2.76 in (7 cm)
Package 1 width	18.27 in (46.4 cm)
Package 1 Length	9.02 in (22.9 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------