

# Product data sheet

## Characteristics

# 9999D01

Contacteur, Definite Purpose, auxiliary contact, 3A at 120 VAC, 1 NC contact, for 50A to 90A DPA contacteurs



### Main

Product Range	DPA
Component type	Auxiliary Contact Module
Used with	contacteur

### Complementary

Auxiliary contact composition	1 NC
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.75 A 480 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A <= 600 V AC resistive control circuit UL 508

### Environment

Product certifications	CSA UL Recognized
------------------------	----------------------




### Ordering and shipping details

Category	21762 - 9999 DISCOUNT CP1B
Discount Schedule	CP1B
GTIN	00785901080879
Nbr. of units in pkg.	1
Package weight(Lbs)	0.07 lb(US) (0.03 kg)
Returnability	Yes
Country of origin	CN

### Packing Units

Package 1 Height	0.70 in (1.778 cm)
Package 1 width	1.70 in (4.318 cm)
Package 1 Length	3.00 in (7.620 cm)

### Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------