



### Main

Range of product	PowerPact L
Product or component type	Mechanical lug
Accessory / separate part category	Connection accessory
Quantity per set	Set of 4
Circuit breaker type	L-Frame

### Complementary

Product compatibility	PowerPact L PowerPact L-Frame
Line Rated Current	400 A
Material	Aluminium
Mounting mode	Unit mount Compression
AWG gauge	500 kcmil copper 500...750 kcmil aluminium
Tightening torque	442.54 Lbf.in (50 N.m) 0.37...0.62 in <sup>2</sup> (240...400 mm <sup>2</sup> ) 500...750 kcmil 442.54 lbf.in (50 N.m) 0.37 in <sup>2</sup> (240 mm <sup>2</sup> ) 500 kcmil



### Environment

Product certifications	UL CSA
------------------------	-----------

### Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CB ACCESS
Discount Schedule	DE2
GTIN	00785901958246
Package weight(Lbs)	35.20 oz (997.903 g)
Returnability	Yes
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>

Contractual warranty

Warranty	18 months
----------	-----------