



## Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	4
Voltage Rating	600 V AC 600 V DC
Wire Size	AWG 6...300 kcmil copper or aluminium

## Complementary

Maximum Width	33.02 in (838.71 mm)
Maximum Height	38 in (965.20 mm)
Maximum Depth	10.63 in (270.00 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil)

## Ordering and shipping details

Category	00133 - DT SWITCH,NEMA3R
Discount Schedule	DE1
GTIN	00785901501701
Nbr. of units in pkg.	1
Package weight(Lbs)	105 lb(US) (47.63 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.96 in (38.001 cm)
Package 1 width	13.00 in (33.02 cm)
Package 1 Length	4.19 in (10.63 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------