Product data sheet Characteristics

NSYSFX20840

SFX 304L stainless suitable enclosure, H2000xW800xD400mm, Scotch Brite® finish.





Main	
Range	Spacial
Product name	Spacial SFX
Enclosure type	Multi-purpose
Category	Suitable enclosure
Nominal height	78.74 in (2000 mm)
Nominal width	31.50 in (800 mm)
Nominal depth	15.75 in (400 mm)
Product installation	Floor-standing
Device composition	structure locking system with handle door mounting plate bracket cable gland plate door with reinforcement frame

\sim				
Cin	mn	lem	en	tarv

Body type	Rear panel integrated	
, ,,	Single piece structure folded and welded	
Door type	Solid	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, handle with 5 mm double-bar insert	
Mounting plate description	Without mounting plate	
Type of gland plate	Plain	
Accessibility for operation	Front	
	Side	
Removable parts	Door by hinges	
	Mounting plate bracket by screws	
	Cable gland plate by clips	
Material	Structure and door stainless steel 304L	
	Handle zamak	
	Hinge stainless steel	
Surface finish	Enclosure Scotch-Brite® brushed	
	Handle painted	
Net Weight	198.42 lb(US) (90 kg)	

Environment

Standards	IEC 62208	
	NEMA 4X	
Product certifications	UL	
IP degree of protection	IP66 IEC 60529	
IK degree of protection	IK10 IEC 62262	
Environmental characteristic	Corrosive	
	Specific hygiene	

Ordering and shipping details

Category	80035 - ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	03606480155680
Nbr. of units in pkg.	1
Package weight(Lbs)	163.9 lb(US) (74.34 kg)
Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	84.25 in (214 cm)	
Package 1 width	33.46 in (85 cm)	
Package 1 Length	20.08 in (51 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------