



## Main

Product	Well-Guard Control
Type	Class 8940 type SS
Device application	Pumping

## Complementary

Control Circuit Type	Common control circuit
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Line Rated Current	45 A
Number of Poles	3
Horsepower Rating	25 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	60 A
Fuse type	R
Thermal overload type	Motor Logic solid state class 10/20
Protection type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical connection	Screw terminal
NEMA size	2
Maximum Height	39.06 in (992 mm)
Maximum Width	15.16 in (385 mm)
Maximum Depth	9.69 in (246 mm)

## Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA

## Ordering and shipping details

Category	21388 - 8940 NSC,NSD
Discount Schedule	CP1
GTIN	00785901163992
Package weight(Lbs)	71 lb(US) (32.21 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------