9001BG301

control station type B - Fast-Slow-Stop - NEMA 1

Green Premium™

Main

Range of product	Harmony 9001B
Product or component type	Complete control station
Device short name	9001BF
Control station application	Three functions
Colour of base of enclosure	Grey

Complementary

Material	Cast zinc
Marking	CE
Type of operator	momentary
Control station composition	1 push-button, white UP-DOWN-STOP 1 push-button
Contacts type and composition	2 NO + 3 NC
Mechanical durability	5000000 cycles
[Ie] rated operational current	5 A 600 V, AC
Device mounting	Flush
Type of installation	Indoor

Environment

Ambient air temperature for storage	-40…158 °F (-40…70 °C)
Ambient air temperature for operation	-13…158 °F (-25…70 °C)
NEMA degree of protection	NEMA 1
Product certifications	UL listed file E42259 CCN NKCR CSA LR25490 class 3211 03

Ordering and shipping details

Category	21421 - 9001 B (NOT BW70 - BW80)
Discount Schedule	CS1
GTIN	00785901857488
Nbr. of units in pkg.	1
Package weight(Lbs)	0.81 lb(US) (0.37 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	12.70 in (32.258 cm)
Package 1 width	5.00 in (12.700 cm)
Package 1 Length	32.26 in (81.935 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric

Approximate Dimensions

0.47
(12)

2.76
(70)

3.69
(94)

0.34
(9)

0.72
(18)

0.48
(12)

1.38
(35)

(2) 0.19
(5) Dia Mtg Holes

2.34
(60)

0.45
(12)

4.09
(104)

5.00
(127)

0.34
(9)

0.72
(16)

0.48
(12)

1.38
(35)

(2) 0.19
(5) Dia Mtg Holes

2.34
(60)

2.06
(52)

1.03
(26)

0.17
(4)

2.53
(64)

0.88
(22)

K.O. for 1/2-3/4 cond.
both ends

2.06
(52)

1.03
(26)

0.17
(4)

2.19   2.41
(56)   (61)

with
mushroom
button

0.88
(22)

K.O. for 1/2-3/4 cond.
both ends