8536SAG12V06

Nonreversing magnetic starter, Size 00, 9 A, 3P, 440/480 VAC 50/60 Hz coil, melting alloy overload, NEMA 1



| Main | | | |
|---------------------------|------------------------|--|--|
| Product or component type | Starter | | |
| Туре | S | | |
| Control Circuit Type | Common control circuit | | |

Complementary

| Complementary | | |
|-------------------------|-----------------------|--|
| Control Circuit Voltage | 440 V AC 50 Hz | |
| | 480 V AC 60 Hz | |
| Motor starter type | Non reversing | |
| Current Rating | 9 A | |
| Number of Poles | 3P | |
| Number of Phases | 3 phase | |
| Horsepower Rating | 1.5 HP 200 V AC | |
| | 1.5 HP 230 V AC | |
| | 2 HP 460 V AC | |
| | 2 HP 575 V AC | |
| Maximum Voltage Rating | 600 V AC | |
| Control Units | No control units | |
| Thermal overload type | Melting alloy 3 | |
| Electrical connection | Screw clamp terminals | |
| NEMA size | 00 | |
| Maximum Height | 10.00 in (254 mm) | |
| Maximum Depth | 5.55 in (141 mm) | |
| Maximum Width | 5.98 in (152 mm) | |
| | | |

Environment

| Enclosure Type | NEMA 1 painted sheet steel |
|------------------------|----------------------------|
| Product certifications | CSA NEMA UL Listed |

Ordering and shipping details

| Category | 21191 - 8502,36 SA,SB(NOT S*R,T,W) | |
|-----------------------|------------------------------------|--|
| Discount Schedule | CP1 | |
| GTIN | 00785901743545 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 7.4 lb(US) (3.36 kg) | |
| Returnability | Yes | |
| Country of origin | MX | |

Packing Units

| Package 1 Height | 6.40 in (16.256 cm) |
|------------------|----------------------|
| Package 1 width | 6.40 in (16.256 cm) |
| Package 1 Length | 10.60 in (26.924 cm) |

Offer Sustainability

| EU RoHS Directive | Not compliant |
|-----------------------|------------------------|
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| Warranty | 18 months | |
|-----------|-----------|--|
| vvairanty | | |