

## Product data sheet

### Characteristics

## 8911DPSG33V06

Starter, Definite Purpose, nonreversing, 30A,  
3 pole, 3 phase, 480 VAC coil, melting alloy  
overload, NEMA 1, +options



### Main

Product	Definite Purpose Starter
Ampere Rating	30 A
Horsepower Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase

### Complementary

Enclosure Material	Painted sheet steel
Enclosure Rating	NEMA 1
Locked Rotor Amperes	180 A 230 V AC 150 A 460 V AC 120 A 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901081517
Nbr. of units in pkg.	1
Package weight(Lbs)	5.9 lb(US) (2.68 kg)
Returnability	Yes
Country of origin	CN

### Packing Units

Package 1 Height	6.70 in (17.018 cm)
Package 1 width	7.00 in (17.780 cm)
Package 1 Length	11.30 in (28.702 cm)

### Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------