

## Product data sheet

### Characteristics

# 8903SMW61V81FF4T

Contacteur, Type S, combination lighting,  
electrically held, 30A, 3 pole, fuse, 110/120  
VAC 50/60 Hz coil, NEMA 4/4X



### Main

Product	Combination electrically held lighting contactor
Type	S

### Complementary

Control Circuit Voltage	480 V AC 60 Hz primary circuit 120 V AC 60 Hz secondary circuit
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Control Circuit Fusing	2 fuses primary circuit 1 fuse secondary circuit
Other Options	None
Disconnecter device type	Fusible disconnect switch R, 30 A 600 V
Electrical connection	Lugs
Maximum Height	24.76 in (629 mm)
Maximum Depth	8.35 in (212 mm)
Maximum Width	9.49 in (241 mm)

### Environment

Enclosure Type	NEMA 4/4X brushed stainless steel surface none
Product certifications	UL listed file E16151 CCN NRNT

### Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901462910
Package weight(Lbs)	36.01 lb(US) (16.33 kg)
Returnability	Yes
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
-------------------	---

### Contractual warranty

Warranty	18 months
----------	-----------