

Main

Product	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	208 V AC 60 Hz
Starter Type	Reversing
Number of Poles	3P
Phase	3 phase
Current Rating	18 A
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460/575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Thermal overload type	Solid state Motor Logic class 10/20
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	5.00 in (127 mm)
Maximum Depth	5.31 in (134.9 mm)
Maximum Width	7.13 in (181.1 mm)

Environment

Enclosure Type	Not rated (open device)
Orientation	Horizontal
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	8.65 lb(US) (3.92 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	18 months
----------	-----------