



### Main

Range	Spacial
Product name	Spacial SBM
Device application	Multi-purpose
Category	Industrial box
Device short name	SBMC
Enclosure type	Entry box
Enclosure nominal height	15.75 in (400 mm)
Enclosure nominal width	31.50 in (800 mm)
Enclosure nominal depth	4.72 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 cover 1 body 6 cover screw 6 FL21 cable gland plate
Body type	Single piece body folded and welded
Type of front cover	Plain door
Cover fixing	Half turn metal screw
Lock type	Captive screw PZ2 outside sealed area
Removable parts	Cover by captive screws Cable gland plate screw

### Complementary

Material	Sheet steel
Surface finish	Polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product certifications	DNV GL UL LR BV
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK10 IEC 62262
Ambient air temperature for storage	-31...140 °F (-35...60 °C)
Operating temperature	-31...176 °F (-35...80 °C)
Net Weight	30.49 lb(US) (13.83 kg)

### Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	03606480520419
Nbr. of units in pkg.	1
Package weight(Lbs)	30.48 lb(US) (13.83 kg)
Returnability	No
Country of origin	IN

## Packing Units

Package 1 Height	32.28 in (820.000 mm)
Package 1 width	16.54 in (420.000 mm)
Package 1 Length	5.71 in (145.000 mm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------