



### Main

Product or component type	Plug-in unit
Range of product	Powerbus

### Complementary

Line Rated Current	100 A
[Ue] rated operational voltage	120/240 V AC
Busbar Configuration	4A L1 + L2 + N + L3
Number of Phases	3 phase
Wiring configuration	4-wire (100 percent neutral)
Circuit Breaker Type	QOU, 30 A, 2 1 breaker
Cable length	Drop cable 3 ft (0.91 m)
Connector type	L6-30

### Environment

NEMA Enclosure Rating	NEMA 1
IP degree of protection	IP40

### Ordering and shipping details

Category	20172-NEW 100A & 225A PLUGS POWERBUS
Discount Schedule	PE8
Package weight(Lbs)	20.00 lb(US) (9.072 kg)
Returnability	No

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>