



### Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	12

### Complementary

Number of ways	12 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	0.71 in (18 mm)
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	80 A 104 °F (40 °C)
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz UL 508
[Uimp] rated impulse withstand voltage	12 kVUL 508
Mounting mode	Horizontal
Mounting location	Top tunnel type terminals
9 mm pitches	24
Maximum Width	8.50 in (216 mm)
Color	White RAL 9001)
Range compatibility	Multi 9 C60 C60 UL489

### Environment

Standards	UL 508
Fire resistance	1760 °F (960 °C) 30 s ) UL 508

### Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	03606480385926
Nbr. of units in pkg.	1
Package weight(Lbs)	0.11 lb(US) (0.05 kg)
Returnability	No
Country of origin	DE

## Packing Units

Package 1 Height	0.520 dm
Package 1 width	1.120 dm
Package 1 Length	2.330 dm

## Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------