

GUPXCB300CD540

GUTOR PXC UL Battery Cabinet, 300A Breaker, 540 Watt/Cell Battery



Overview

Presentation	Fully populated, VRLA battery cabinets. Includes all breakers and fuses, line up and match capability, top and/or bottom cable entry.
Lead time	Usually Ships within 6 Weeks

Physical

Maximum Depth	31.50 in (80 cm)
Maximum Height	82.72 in (210.1 cm)
Net Weight	3900.00 lb(US) (1769.01 kg)
Maximum Width	39.69 in (100.8 cm)

Conformance

Standards	FCC Part 15 class A UL 1778
-----------	--------------------------------

Environmental

Ambient air temperature for operation	14...104 °F (-10...40 °C)
Operating altitude	0...9842 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Storage altitude	0...16404 ft (0.00...4999.94 m)

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	C&D and EnerSys
Device mounting	Enclosed battery cabinet
Battery type	VRLA
Battery Volt-Amp-Hour Capacity	0 VAh

Ordering and shipping details

Package weight(Lbs)	4000.00 lb(US) (1814.37 kg)
---------------------	-----------------------------

Packing Units

Package 1 Height	90.71 in (230.4 cm)
Package 1 width	54.02 in (137.2 cm)
Package 1 Length	38.50 in (97.8 cm)
Number of Units in Package 3	1

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------