



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|



Environment

| | |
|---------------------------------------|----------------------------------|
| Ambient air temperature for operation | 32...131 °F (0...55 °C) |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -13...167 °F (-25...75 °C) |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |

Physical

| | |
|---------------------|------------------------|
| Color | Black |
| Maximum Depth | 12.99 in (33 cm) |
| Maximum Height | 1.73 in (4.4 cm) |
| Net Weight | 14.84 lb(US) (6.73 kg) |
| Number of rack unit | 1U |
| Maximum Width | 19.02 in (48.3 cm) |

Input

| | |
|----------------------------|---|
| Input Frequency | 45...65 Hz |
| Line Rated Current | 32 A |
| Number of input connectors | 1 Hard Wire 3-wire |
| Acceptable Input Voltage | 180...264 V |
| Max line current | 32 A |
| Input current limits | 32 A |
| Load Capacity | 6000 VA |
| Nominal Input Voltage | 200 V 208 V 220 V 230 V 240 V |

Output

| | |
|--------------------------------------|---|
| Maximum Total Current Draw per Phase | 32 A |
| Output connector type | Hard Wire 3-wire (H N + E) 1 |
| Output voltage | 200 V 208 V 220 V 230 V 240 V |
| Product web sub-family | 208 V 220 V 230 V 240 V |
| Connections - terminals | 2 screw terminal |

Conformance

| | |
|------------------------|-----|
| Product certifications | DNV |
|------------------------|-----|



Ordering and shipping details

| | |
|---------------------|------------------------|
| GTIN | 00731304284703 |
| Package weight(Lbs) | 18.23 lb(US) (8.27 kg) |

Packing Units

| | |
|------------------------------|--------------------|
| Package 1 Height | 2.99 in (7.6 cm) |
| Package 1 width | 22.01 in (55.9 cm) |
| Package 1 Length | 15.98 in (40.6 cm) |
| Number of Units in Package 3 | 60 |

Offer Sustainability

| | |
|----------------------------|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |

Contractual warranty

| | |
|----------|--------------------------------|
| Warranty | 2 year (manufacturer's defect) |
|----------|--------------------------------|