# XCSL724B3 INTERLOCK SWITCH 300VAC 10AS XCSL



#### Main

Device short name	XCSL	
Enclosure type	Water resistant enclosure indoor/outdoor Dustproof enclosure indoor/outdoor Ice/sleet proof enclosure indoor/outdoor	

## Complementary

Complementary		
Line Rated Current	10 A	
[Us] rated supply voltage	24 V DC	
Actuator	Key	
Contact operation	Slow-break, break before make	
Contacts type and composition	1 NO staggered 2 NC	
Maximum Depth	1.73 in (43.94 mm)	
Enclosure material	metal	
Height	7.64 in (194.06 mm)	
Installation direction	Electromagnet connection left Actuator supply right	
Key locking position	On the right	
Locking options description	With locking of actuator, unlocking by key operated lock	
Number of poles	3	
Permissible voltage	300 V AC	
Pilot light	LED orange	

#### Environment

Ambient air temperature for operation	-13158 °F (-2570 °C)
IP degree of protection	IP67
NEMA degree of protection	NEMA 1/2/3/4/12
Product certifications	CE UL listed file E164353 CCN NKCR CSA LR4408794 class 3211 03

### Ordering and shipping details

22411-LIMIT SWITCHES,IEC,XCKJ
Т
00785901274780
19.20 oz (544.311 g)
No
FR

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

<u></u>		
Warranty	18 months	