Product data sheet Characteristics

792XDX3C-110D

Power relay, Legacy, 4PDT, 3A, 110 VDC, low level bifurcated contacts, clear cover





Main

| | Product range | Legacy |
|--|---------------------|-------------|
| | Product type | Relay |
| | Switch function | 4PDT |
| | Contact composition | 4 NO + 4 NC |
| | | |

Complementary

| Complementary | |
|--------------------------------|--|
| Input current | 3 A |
| Contacts material | Gold plated bifurcated silver |
| Local signalling | Flag |
| Minimum switching current | 3 mA 5 V |
| Coil Resistance | 13440 Ohm |
| Input voltage | 110 V DC |
| Drop-out voltage threshold | >= 0.15 Uc AC >= 0.1 Uc DC |
| [le] rated operational current | 3 A 240/277 V AC UL 3 A 120 V AC UL 3 A 30 V DC UL 2 A AC-1 NO)IEC 2 A DC-1 NO)IEC 1 A AC-1 NC)IEC 1 A DC-1 NC)IEC |
| Average coil consumption in VA | 0.8 DC |
| Voltage range | 0.81.1 Un AC/DC |
| Maximum switching voltage | 300 V UL 300 V CSA 250 V IEC |
| Maximum Horse Power Rating | 0.0625 hp 120 V AC |
| Connections - terminals | Faston connectors |
| Mounting | Panel DIN rail |
| Height | 1.37 in (34.8 mm) |
| Width | 0.83 in (21 mm) |
| Depth | 1.07 in (27.2 mm) |
| Net Weight | 1.31 oz (37 g) |
| Operating time | 25 ms 20 ms at maximum rated voltage |
| | |

Environment

| Ambient temperature range - operational | -40131 °F (-4055 °C) |
|---|--|
| Ambient air temperature for storage | -40185 °F (-4085 °C) |
| Product certifications | UL CSA CE |
| Electrical durability | 100000 cycles resistive |
| Mechanical durability | 10000000 cycles |
| Dielectric strength | 2000 V AC between coil and contact 2000 V AC between poles 1300 V AC between contacts |
| Shock resistance | 10 gn in operation 30 gn not operating |
| Vibration resistance | 3 gn 35150 Hz)operating +/- 1 mm 1035 Hz)operating 5 gn 35150 Hz)not operating +/- 1 mm 1035 Hz)not operating |
| Surge withstand duration | 1.2/50 μs |
| | |

Ordering and shipping details

| GTIN | 03606480781582 |
|-------|----------------|
| 01.11 | 00000100101002 |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | ₫Yes |
| China RoHS Regulation | ☑ China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |