


Panel Thickness E dim. inches (mm)	Number of Gasket
1/16 (1.6)	4
1/8 (3.2)	3
3/16 (4.8)	2
1/4 (6.4)	1



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
9001KS11K1CH501

Schneider Electric
Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone:+1 8773425173
Email: CCC@us.schneider-electric.com

Technical Information:
UL File: E78403 CCN NKCR
CSA File: LR24590 Class 3211-03
CE Marked: Yes
RoHS: Yes
NEMA / IP Rating: NEMA 1/2/3/3R/4/6/12/13 Water tight, Dust tight and Oil tight (Indoor/Outdoor), IP66
Key Number: CH501
Key Removal: Left Only
Light Module Supply Voltage: not applicable
Light Module Type: not applicable
Number of Operators: 1

Description:
Ring Nut Material: 30mm Selector Switch
Operator Type: Chromium Plated Zinc
Operator Action: Non-Illuminated
Button Type: Maintained
Guard Type: n/a
Button/Cap Color: n/a
Lens Type: n/a
Lens Color: not applicable
Knob Type: not applicable
Knob Color: Key Operated Knob
Number of Positions: Key
2

Specification: