



### Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

### General

Provided equipment	EcoStruxure IT ready (UPS)
--------------------	----------------------------

### Physical

Color	White
Maximum Depth	300.00 in (762 cm)
Maximum Height	118.11 in (300 cm)
Net Weight	22046.24 lb(US) (10000 kg)
Number of racks	5
Rack Free Space	210
Number of rack unit	42U
Maximum Width	137.99 in (350.5 cm)

### Input

Nominal Input Voltage	3 phase
-----------------------	---------

### Output

Kw Rating	40000 W
KW per Rack	8 kW
Output voltage	208 V 3 phase
PDU Type	Metered
Max Configurable Power (Watts)	40000 W
Configured Power	40000 W

### Conformance

Product certifications	UL Listed
------------------------	-----------

### Environmental

Ambient air temperature for operation	-11...131 °F (-24...55 °C)
Operating altitude	0...10000 ft

## Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery type	VRLA
Liquid Electrolyte Value	0
Battery Volt-Amp-Hour Capacity	0 VAh

## Communications & Management

Emergency Power Off (EPO)	Optional
---------------------------	----------

## Ordering and shipping details

Package weight(Lbs)	15432.37 lb(US) (7000 kg)
---------------------	---------------------------

## Packing Units

Package 1 Height	118.11 in (300 cm)
Package 1 width	137.99 in (350.5 cm)
Package 1 Length	300.00 in (762 cm)

## Contractual warranty

Warranty	1 year (parts only)
----------	---------------------