

ACCD75235

Condenser 1x1 Build to Order, 38kW, 95F,
460V/3, 60Hz (QSCE55319)



Main

Audible noise at 1 meter from surface of unit	59 dBA
Air flow	5400 ft³/min (2548.52 l/s)
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Maximum Depth	80.91 in (205.5 cm)
Maximum Height	54.61 in (138.7 cm)
Input power	1450 W
Nominal Input Voltage	3 phase 3 phase 3 phase 3 phase
Inrush current	10 A
Length	6.74 ft (2.05 m)
Maximum Overcurrent Protection	15 A
Minimum Circuit Amp Capacity	4 A
Mounting mode	Not rack-mountable
Mounting preference	No preference
Input Frequency	60 Hz
Operating altitude	0...10000 ft
Product certifications	ETL
Net Weight	551.00 lb(US) (249.93 kg)
Return pipe diameter	0.88 in (22.35 mm)
Supply pipe diameter	0.63 in (16.00 mm)
Maximum Width	48.94 in (124.3 cm)
Air Discharge Patterns	Horizontal Upflow
Product web sub-family	Heat rejection

Ordering and shipping details

Package weight(Lbs)	690.00 lb(US) (312.98 kg)
---------------------	---------------------------

Packing Units

Package 1 Height	65.98 in (167.6 cm)
Package 1 width	55.00 in (139.7 cm)
Package 1 Length	85.00 in (215.9 cm)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------