



### Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 750XBXR Relay 750BXXH
Number of terminals	8
Switch function	DPDT
Contact composition	2 NO + 2 NC

### Complementary

Line Rated Current	10 A 15 A
Rated voltage	300 V 600 V
Contact terminal arrangement	Mixed
Connections - terminals	Output screw clamp terminalssolid Output screw clamp terminalsstranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw < 1 N.m Screw < 0.8 N.m
Fixing mode	By screw M3.5, M3.5 panel By screws, M3 panel
Shape of screw head	Combination roundhead
Net Weight	1.41 oz (40 g)
Width	1.57 in (40 mm)
Depth	2.24 in (57 mm)

### Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

### Ordering and shipping details

GTIN	03606480277962
------	----------------

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.