

Product data sheet

Characteristics

8903SMW81V02

Contactor, Type S, combination lighting,
electrically held, 30A, 3 pole, breaker, 110/120
VAC 50/60 Hz coil, NEMA 4/4X



Main

Product	Combination electrically held lighting contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnecter device type	Thermal magnetic circuit breaker, 30 A 600 V
Electrical connection	Lugs
Maximum Height	24.76 in (629 mm)
Maximum Depth	8.35 in (212 mm)
Maximum Width	9.49 in (241 mm)

Environment

Enclosure Type	NEMA 4/4X brushed stainless steel surface none
Product certifications	UL listed file E16151 CCM NRNT

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
Package weight(Lbs)	33.36 lb(US) (15.13 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------