

Main

Device short name	FHG
Enclosure type	Standard environment enclosure indoor
Product specific application	Control small electrically driven air compressors
Range of product	Square D Pumptrol

Complementary

Adjustable range on rising pressure	40...100 psi (275.79...689.48 kPa)
Approximate fixed differential	20 psi (137.90 kPa)
Contact code designation	A600
Maximum Depth	2.78 in (70.61 mm)
Electrical connection	Screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Maximum Height	2.8 in (71.12 mm)
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	220 psig
Maximum Horse Power Rating	2 Hp 115 V AC, 3 phase 2 Hp 230 V AC, 1 phase 3 Hp 230 V AC, 3 phase 1 Hp 460/575 V AC, 3 phase 1.5 hp 115 V AC, 1 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Net Weight	1.13 lb(US) (0.51 kg)
Scale type	Fixed differential
Switch function	DPST
Maximum Width	3.76 in (95.50 mm)

Environment

NEMA degree of protection	NEMA 1
Product certifications	CSA LR25490 class 3211 06 UL listed file E12158 CCN NKPZ

Ordering and shipping details

Category	21533-9013 FHG (INDIVIDUAL-DISCOUNT CP7I)
Discount Schedule	CP7I
GTIN	00785901177449
Package weight(Lbs)	16.00 oz (453.592 g)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------