Product data sheet Characteristics

8903SMC62V02C

Contactor, NIGHT MASTER, combination lighting, 30A, 3 pole, fuse, 110/120 VAC 50/60 Hz coil. NEMA 3R, +options

Main

Type	Night-Master	
------	--------------	--

Complementary

Control Circuit Voltage	120 V AC 60 Hz	
	110 V AC 50 Hz	
Current Rating	30 A	
Number of Poles	3P	
Control Units	Selector switch 3 positions HAND-OFF-AUTO)	
Auxiliary Contacts	Without	
Other Options	None	
Disconnector device type	Fusible disconnect switch R, 30 A 250 V	
Electrical connection	Lugs	
Maximum Height	23.50 in (597 mm)	
Maximum Depth	10.51 in (267 mm)	
Maximum Width	15.00 in (381 mm)	

Environment

Enclosure Type	NEMA 3R painted sheet steel surface none
Product certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21326 - 8903 S*C
Discount Schedule	CP1
Package weight(Lbs)	105 lb(US) (47.63 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty	
Warranty	18 months