



Overview

Lead time	Usually in Stock
-----------	------------------

Environment

Ambient air temperature for operation	32...131 °F (0...55 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...167 °F (-25...75 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Physical

Color	Black
Maximum Depth	12.99 in (33 cm)
Maximum Height	1.73 in (4.4 cm)
Net Weight	14.84 lb(US) (6.73 kg)
Number of rack unit	1U
Maximum Width	19.02 in (48.3 cm)

Input

Input Frequency	45...65 Hz
Line Rated Current	50 A
Number of input connectors	1 Hard Wire 3-wire
Acceptable Input Voltage	100...240 V
Max line current	50 A
Input current limits	50 A
Load Capacity	6000 VA
Nominal Input Voltage	200 V 208 V 220 V 230 V 240 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Output

Maximum Total Current Draw per Phase	50 A
Output connector type	Hard Wire 3-wire (H N + E) 1
Output voltage	200 V 208 V 220 V 230 V 240 V
Product web sub-family	208 V 220 V 230 V 240 V
Connections - terminals	2 screw terminal

Conformance

Product certifications	DNV
------------------------	-----



Ordering and shipping details

GTIN	00731304324836
Package weight(Lbs)	18.23 lb(US) (8.27 kg)

Packing Units

Package 1 Height	2.99 in (7.6 cm)
Package 1 width	22.01 in (55.9 cm)
Package 1 Length	15.98 in (40.6 cm)
Number of Units in Package 3	60

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	2 year (manufacturer's defect)
----------	--------------------------------