



Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	27 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	3 HP 115 V AC 5 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	Selector switch (HAND-OFF-AUTO)
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	1P
Maximum Height	12.76 in (324 mm)
Maximum Depth	8.54 in (217 mm)
Maximum Width	6.38 in (162 mm)


Environment

Enclosure Type	NEMA 12 painted sheet steel
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901928461
Package weight(Lbs)	14.81 lb(US) (6.72 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant

Contractual warranty

Warranty	18 months
----------	-----------