

### Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

### Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	27 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	3 HP 115 V AC 5 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	1P
Maximum Height	6.77 in (172 mm)
Maximum Depth	4.21 in (107 mm)
Maximum Width	3.50 in (89 mm)



### Environment

Enclosure Type	Not rated (open device)
Product certifications	UL Listed NEMA CSA

### Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	5 lb(US) (2.27 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------