

# Product data sheet

## Characteristics

# 70-124-2

Socket, Legacy general purpose relay  
accessory, 3PDT, 15A, 300 V, 11 pins, Quick  
connect terminal, 788R series



### Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 788XBXR/XCXR
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

### Complementary

Line Rated Current	15 A
Rated voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Output Faston terminals
Fixing mode	By screw chassis By screw panel
Net Weight	0.43 oz (12.1 g)
Depth	2.03 in (51.45 mm)

### Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0

### Ordering and shipping details

GTIN	03606480277764
------	----------------

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.