

LHL26250

LHL LH MOLDED CASE CIRCUIT BREAKER,600VAC/250VDC, 250A, 2P



Main

Product or component type	Circuit breaker
Trip Unit Type	Thermal-magnetic
Rating Code	H

Complementary

Line Rated Current	250 A
Number of Poles	2P
Interrupt Rating	25 KA 600 V AC 65 KA 240 V AC 35 KA 480 V AC 50 KA 250 V DC 50 kA 125 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)
Tightening torque	115.06 Lbf.in (13 N.m) 0.07...0.47 in ² (42...304 mm ²) AWG 1...600 kcmil) 115.06 lbf.in (13 N.m) 0.07...0.20 in ² (42...127 mm ²) AWG 1...250 kcmil)

Environment

Product certifications	IEC UL Listed CSA
------------------------	-------------------------

Ordering and shipping details

Category	00935-LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901358626
Package weight(Lbs)	14.46 lb(US) (6.560 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------