

# Product data sheet

## Characteristics

# 8903PBV10BV39

panelboard lighting contactor, 200 AMP, 2 pole, bus mount, 240/277V 60Hz coil



### Main

Product	Mechanically Held Lighting Contactor
Type	PB
Control Circuit	Common control circuit

### Complementary

Control Circuit Voltage	240/277 V AC 60 Hz
Line Rated Current	200 A
Number of Poles	2P
AWG gauge	350 kcmil aluminium/copper)power AWG 18...AWG 10 copper)control
Maximum Overall Voltage	600 V AC
Auxiliary contact composition	Without
Mounting support	busbar
Electrical connection	Busbar connection
Maximum Height	9.49 in (241 mm)
Maximum Depth	3.39 in (86 mm)
Maximum Width	7.52 in (191 mm)

### Environment

Product certifications	UL Listed CSA
------------------------	------------------

### Ordering and shipping details

Category	21323 - 8903 PB
Discount Schedule	CP1
GTIN	00785901079941
Package weight(Lbs)	24.7 lb(US) (11.20 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------