



Overview

Presentation	This unique Y cable takes a single C20 input and splits it into two C19 outlets. This allows for multiple outputs to be connected to a single output on a rack PDU
Lead time	Usually in Stock

Physical

Cable length	6 ft (1.83 m)
Color	Black
Maximum Depth	3.50 in (8.9 cm)
Maximum Height	2.01 in (5.1 cm)
Net Weight	1.41 lb(US) (0.64 kg)
Maximum Width	10.51 in (26.7 cm)

Input

Plug standard	IEC 60320 C20
Max line current	20 A
Input current limits	20 A

Output

Number of power socket outlets	1 IEC 60320 C19
Output voltage	208 V

Conformance

Product certifications	UL Listed
------------------------	-----------

Environmental

Ambient air temperature for operation	14...104 °F (-10...40 °C)
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	50...86 °F (10...30 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304241751
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	3.39 in (8.6 cm)
Package 1 width	12.76 in (32.4 cm)
Package 1 Length	4.02 in (10.2 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------