9001SKP3G31 PILOT LIGHT 220VAC 30MM SK +OPTIONS





Main	
Bezel material	Black plastic
Device short name	SK
Enclosure type	Corrosion resistance enclosure indoor/outdoor Dust and oil resistant weatherproof enclosure indoor/ outdoor
Lens type	Fresnel plastic
Mounting diameter	1.18 in (30 mm)

Complementary

Cap/operator or lens colour	Green	
Electrical connection	Screw clamp terminal	
Light block supply	Via transformer 208 V AC 50/60 Hz Via transformer 220 V AC 50/60 Hz	
Operating mode	Normal	
Shape	Round head	

Environment

NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
Product certifications	CE UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03

Ordering and shipping details

Category	21429-9001 SK,SKY	
Discount Schedule	CS1	
Package weight(Lbs)	8.00 oz (226.796 g)	,
Returnability	No	
Country of origin	MX	

Offer Sustainability

Green Premium product	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope)	
Yes	
Yes	
₽¥Yes	
China RoHS Declaration	
Product Environmental Profile	
☑ End Of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Warranty 18 months