



Main

| | |
|---------------------------|----------------------------------|
| Range of product | Harmony 9001K |
| Product or component type | Complete illuminated push-button |
| Device short name | 9001K |
| Bezel material | Chromium plated metal |
| Mounting diameter | 1.18 in (30 mm) |
| Light source | Yellow LED |

Complementary

| | |
|------------------------------|-----------------------------|
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | Yellow projecting, unmarked |
| Bulb base | BA 9s |
| Light block supply | Direct 24...28 V AC/DC |
| Mechanical durability | 5000000 cycles |
| Operating position | Any position |
| Net Weight | 0.37 lb(US) (0.166 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | UL 508 JIS C 4520 JIS C 852 EN/IEC 60947-5-1 EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-1 |
| Product certifications | NEMA UL 508 |
| Protective treatment | TC |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |
| Electrical shock protection class | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 |

Ordering and shipping details

| | |
|-----------------------|-------------------------------|
| Category | 21426 - 9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 00785901843009 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.5 lb(US) (0.23 kg) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------|----------------------|
| Package 1 Height | 5.08 in (12.903 cm) |
| Package 1 width | 2.00 in (5.080 cm) |
| Package 1 Length | 12.90 in (32.774 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|