



Main

Range of product	Harmony iPC
Product or component type	External power supply module
Accessory / separate part category	Electrical accessory

Complementary

Accessory / separate part destination	HMIDAD modular display adaptor HMIPSP S-Panel PC performance HMIPSO S-Panel PC optimised
Input voltage	90...260 V AC 47...63 Hz
Input current	1600 mA 100 V AC
Output voltage	24 V DC
Line Rated Current	2.62 A
Inrush current	70 A 230 V AC

Environment

Ambient air temperature for operation	32...158 °F (0...70 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	0...95 % non-condensing
Product certifications	CE CSA 60950 CULus UL 60950

Ordering and shipping details

Category	22575 - MAGELIS MC3
Discount Schedule	MC3
GTIN	00785901518853
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2 lb(US) (1.00 kg)
Returnability	No
Country of origin	TW

Packing Units

Package 1 Height	1.36 in (34.500 mm)
Package 1 width	2.05 in (52.000 mm)
Package 1 Length	4.65 in (118.000 mm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.