Product data sheet Characteristics

9001KS11BH56 SELECTOR SWITCH 600VAC 10A 30MM T-K

Main

| Bezel material | Chromium plated metal |
|-------------------|-----------------------|
| Device short name | К |
| Mounting diameter | 1.18 in (30 mm) |

Complementary

| Line Rated Current | 10 A | |
|-------------------------------|--------------------------|--|
| Operator position information | 2 positions | |
| Operator profile | Standard knob | |
| Operator profile | 1 projecting push-button | |
| Utilisation category | AC-15 | |
| | DC-13 | |

Environment

| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13 |
|---------------------------|---|
| Product certifications | CE UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03 |

Ordering and shipping details

| Category | 21426 - 9001 K (NOT KA,KM,KX) | |
|---------------------|-------------------------------|--|
| Discount Schedule | CS1 | |
| GTIN | 00785901493327 | |
| Package weight(Lbs) | 0.5 lb(US) (0.23 kg) | |
| Returnability | No | |
| Country of origin | MX | |
| | | |

Contractual warranty

| Contractual warranty | | | |
|----------------------|-----------|--|--|
| Warrantv | 18 months | | |