ABE9C1240M

IP67 passive splitter box - with 4 channels M12 connector





Main

Range of product	Advantys ABE9
Product or component type	IP67 passive splitter box
Number of channels	4
Electrical connection	1 male plug-in connector 4 female connectors M12 5 pins
Status LED	without

Complementary

8 ways	
24 V DC	
4 A	
Category 3 VDE 0110	
Any position	
M4 screw fixing	
5000 μOhm	
16 A 0.00 in² (1 mm²) 12 A 0.00 in² (0.75 mm²)	
Without or with	
0.13 lb(US) (0.06 kg)	
	24 V DC 4 A Category 3 VDE 0110 Any position M4 screw fixing 5000 μOhm 16 A 0.00 in² (1 mm²) 12 A 0.00 in² (0.75 mm²) Without or with

Environment

IP degree of protection	IP67 IEC 529	
Product certifications	CULus	
Ambient air temperature for operation	-4176 °F (-2080 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Vibration resistance	0.2 gn 57150 Hz)IEC 68-2-6, FC tests	
Shock resistance	30 gn 11 ms EN 68-2-2 30 gn 11 ms IEC 68-2-2	:

Ordering and shipping details

Category	18125 - MODSOFT LITE SOFTWARE
Discount Schedule	PC12
GTIN	00785901583776
Nbr. of units in pkg.	1
Package weight(Lbs)	0.21 lb(US) (0.10 kg)
Returnability	No
Country of origin	DE

Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	2.28 in (5.8 cm)
Package 1 Length	6.10 in (15.5 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	5.78 lb(US) (2.624 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability


Green Premium product WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
		Yes
		₽¥Yes
China RoHS Declaration		
Product Environmental Profile		
End Of Life Information		
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.		

Contractual warranty

Warranty	18 months


ABE9C1240M

Dimensions with ABE9XCA14 •• Connector



ABE9C1240M

Wiring Diagram



(1) BR1 and BR2: removable link

Item	Terminal	Wire
1/4	1	White
1/2	9	Grey/pink
2/4	2	Green
2/2	10	Red/blue
3/4	3	Yellow
3/2	11	White/green
4/4	4	Grey
4/2	12	Brown/green
1 and 3/1	+1	Brown 1
2 and 4/1	+2	Brown 2
1 and 3/3	-1	Blue 1
2 and 4/3	-2	Blue 2
14/5	PE	Green/yellow

Connection Terminals

