



Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1D8
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	480 V AC 50/60 Hz
Average resistance	32249 Ohm 68 °F (20 °C)
Inductance of closed circuit	938.41 H
Product compatibility	LC1D115 LC1D150
Mechanical durability	8 Mcycles
Maximum operating rate	1200 cyc/h 140 °F (60 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out 0.3...0.5 Uc 50/60 Hz 131 °F (55 °C) Operational 0.8...1.15 Uc 50/60 Hz 131 °F (55 °C)
Inrush power in VA	280...350 VA 60 Hz 0.9 68 °F (20 °C)) 280...350 VA 50 Hz 0.9 68 °F (20 °C))
Hold-in power consumption in VA	2...18 VA 60 Hz 0.9 68 °F (20 °C)) 2...18 VA 50 Hz 0.9 68 °F (20 °C))
Heat dissipation	3...4.5 W 50/60 Hz

Environment

Ambient air temperature for operation	23...140 °F (-5...60 °C)
---------------------------------------	--------------------------

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901303756
Nbr. of units in pkg.	1
Package weight(Lbs)	0.7 lb(US) (0.32 kg)
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.44 in (6.2 cm)
Package 1 width	4.53 in (11.5 cm)
Package 1 Length	6.69 in (17 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to www.p65warnings.ca.gov
---------------------------	---

Contractual warranty

Warranty	18 months
----------	-----------