Product data sheet Characteristics

VW3M9415

preassembled cable for STO safety function - 15 m - M8





Main	
Range of product	Lexium 32i
Product or component type	Cable
Accessory / separate part category	Connection accessory
Product compatibility	Connector module VW3M91 safe torque off safety function Connector module VW3M92 safe torque off safety function

Complementary

Complementary		
Cable length	49.21 ft (15 m)	
Electrical connection	M8 female connector, 1 Free end, 1	
Cable composition	3 x 0.34 mm²	
Standards	IEC 61800-5-2	
Wire colour	White STO_A Brown STO_B Green STO_COM	
Net Weight	1.12 lb(US) (0.51 kg)	

Ordering and shipping details

18289 - LEXILIM INTEGRATED DRIVES ACC	
10203 - EEXIOW INTEGRATED DRIVES AGO	
PC56	
03606480595608	
1	
1 lb(US) (0.45 kg)	
No	
CZ	
	03606480595608 1 1 Ib(US) (0.45 kg) No

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.97 in (5 cm)	
Package 1 width	11.81 in (30 cm)	
Package 1 Length	16.93 in (43 cm)	
Unit Type of Package 2	S04	
Number of Units in Package 2	6	
Package 2 Weight	8.88 lb(US) (4.028 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information