ZB5AH83

yellow projecting illuminated pushbutton head Ø22 push-push for integral LED





Main

| Range of product | Harmony XB5 |
|-------------------------------|----------------------------------|
| Product or component type | Head for illuminated push-button |
| Product compatibility | Integral LED |
| Device short name | ZB5 |
| Bezel material | Dark grey plastic |
| Mounting diameter | 0.87 in (22 mm) |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Type of operator | push-push |
| Operator profile | Yellow projecting, unmarked |

Complementary

| CAD overall width | 1.14 in (29 mm) | _ |
|-----------------------------|---|---|
| CAD overall height | 1.14 in (29 mm) | |
| CAD overall depth | 1.30 in (33 mm) | |
| Net Weight | 0.04 lb(US) (0.017 kg) | |
| Mechanical durability | 500000 cycles | |
| Station name | XALD 15 cut-outs XALK 25 cut-outs | |
| Electrical composition code | M5 2 single front mounting integral LED M6 2 single front mounting integral LED and transformer M10 2 single front mounting integral LED MF1 2 single front mounting integral LED MR1 2 single rear mounting integral LED | |
| Device presentation | Basic element | |

Environment

| Livilorit | |
|---------------------------------------|---|
| Protective treatment | TH |
| Ambient air temperature for storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -40158 °F (-4070 °C) |
| Electrical shock protection class | Class II IEC 60536 |
| IP degree of protection | IP66 IEC 60529 IP69 IP69K |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| IK degree of protection | IK05 IEC 50102 |
| Standards | EN/IEC 60947-5-1 UL 508 JIS C8201-5-1 CSA C22.2 No 14 EN/IEC 60947-5-4 EN/IEC 60947-5-5 EN/IEC 60947-1 JIS C8201-1 |

| Product certifications | CSA | |
|------------------------|--|--|
| | UL Listed | |
| | GL | |
| | LROS (Lloyds register of shipping) | |
| | BV | |
| | RINA | |
| | DNV | |
| Vibration resistance | 5 gn 2500 Hz)IEC 60068-2-6 | |
| Shock resistance | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 | |
| | , | |

Ordering and shipping details

| GTIN | 03606481206473 |
|---------------------|------------------------|
| Package weight(Lbs) | 0.03 lb(US) (0.014 kg) |

Packing Units

| Package 1 Height | 0.420 dm |
|------------------|----------|
| Package 1 width | 0.330 dm |
| Package 1 Length | 0.520 dm |

Offer Sustainability

| Offer Sustainability | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | €Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | [©] End Of Life Information |
| | |