ZBW040D69

blue light block for head Ø22 for BA9s bulb 230...240V screw terminal for lugs



Main Range of product Harmony XB5 Harmony XB4 Product or component Light block ZBW Device short name Connections - terminals Screw terminals for lug Signalling type Steady LED Light source Bulb base BA 9s Light block supply Integrated transformer 6 V Blue Light source colour 230...240 V AC 50/60 Hz [Us] rated supply

Complementary

Supply voltage limits	195264 V AC
Current consumption	14 mA
Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV IEC 61000-4-5

voltage

Environment

Environment		
Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
IP degree of protection	IP20 IEC 60529	
Standards	EN/IEC 60947-5-5 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-1 CSA C22.2 No 14 EN/IEC 60947-5-1 JIS C8201-5-1 JIS C8201-1	
Resistance to fast transients	2 kV IEC 61000-4-4	
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3	
Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2	
Electromagnetic emission	Class B IEC 55011	

Ordering and shipping details

GTIN	03389110178494
Package weight(Lbs)	0.29 lb(US) (0.131 kg)

Packing Units

Package 1 Height	0.880 dm
Package 1 width	0.340 dm
Package 1 Length	0.540 dm

Warranty 18 months